

ROOMSIDE REPLACEABLE TERMINAL FILTER CEILING MODULE



Engineered Simplicity

Quick Installation

Quick Replacement

Easy to Handle

Requires No Tools to install or replace

PERMA-HOOD™
U.S. PATENT 6,267,793B1

- Roomside Adjustable Aluminum Damper (integral with filter)
- Gel Seal Filter Frame (Anodized Extruded Aluminum)
- Knife Edge Housing
- Face Guard (Epoxy Coated Steel) is integral with filter
- Large Filter Face Area
- 10" or 12" Collar
- Available in any efficiency up to 99.9999995% @ .12 micron
- Available in a Motorized (FFU) version



PERFORMANCE CHOICES


- 1) FOR STANDARD PERFORMANCE SPECIFY THE **HHR250** SERIES.
- 2) FOR IMPROVED PERFORMANCE SPECIFY THE **HHR400** SERIES
- 3) SPECIFY THE **HHR500** SERIES AND ACHIEVE ULPA PERFORMANCE AT HEPA PRICES, 50% LOWER **POWER** (HORSEPOWER/KILOWATT HOURS) CONSUMPTION AND 3 TIMES THE LIFE OF THE INDUSTRY STANDARD FILTERS WITH NO REDUCTION IN CFM.

HHR250 SERIES SPECIFICATIONS

INDUSTRY STANDARD

Example

Series Number	Size	Actual Inches	99.99% @ .12 Micron Static Pressure 100FPM	WT.#
HHR250-2	24 x 24	23 ⁵ / ₈ x 23 ⁵ / ₈ x 5 ⁷ / ₈	.48" W.G.	20
HHR250-3	24 x 36	23 ⁵ / ₈ x 35 ⁵ / ₈ x 5 ⁷ / ₈	.48" W.G.	30
HHR250-4	24 x 48	23 ⁵ / ₈ x 47 ⁵ / ₈ x 5 ⁷ / ₈	.48" W.G.	40



For lower ΔP, specify HHR250E (enhanced)

When ordering, please use the appropriate **SERIES NUMBER** and specify the following:


- 1) Collar diameter – 10" or 12"
- 2) Efficiency % – refer to graph
- 3) Other options
- 4) Exact dimensions if other than shown
- 5) Static pressure and efficiency if other than shown

HHR400 SERIES SPECIFICATIONS

IMPROVED PERFORMANCE

Example

Series Number	Size	Actual Inches	99.999% @ .12 Micron Static Pressure 100FPM	WT.#
HHR400-2	24 x 24	23 ⁵ / ₈ x 23 ⁵ / ₈ x 8 ⁷ / ₈	.43" W.G.	25
HHR400-3	24 x 36	23 ⁵ / ₈ x 35 ⁵ / ₈ x 8 ⁷ / ₈	.43" W.G.	38
HHR400-4	24 x 48	23 ⁵ / ₈ x 47 ⁵ / ₈ x 8 ⁷ / ₈	.43" W.G.	50



For lower ΔP, specify HHR400E (enhanced)

When ordering, please use the appropriate SERIES NUMBER and specify the following:

- 1) Collar diameter – 10" or 12"
- 2) Efficiency % – refer to graph
- 3) Other options
- 4) Exact dimensions if other than shown
- 5) Static pressure and efficiency if other than shown


HHR500 SERIES SPECIFICATIONS

LOWEST OPERATING COST

Example



Series Number	Size	Actual Inches	99.999% @ .12 Micron Static Pressure 100FPM	WT.#
HHR500-2	24 x 24	23 ⁵ / ₈ x 23 ⁵ / ₈ x 8 ⁷ / ₈	.26" W.G.	30
HHR500-3	24 x 36	23 ⁵ / ₈ x 35 ⁵ / ₈ x 8 ⁷ / ₈	.26" W.G.	45
HHR500-4	24 x 48	23 ⁵ / ₈ x 47 ⁵ / ₈ x 8 ⁷ / ₈	.26" W.G.	60



For lower ΔP, specify HHR500E (enhanced)

When ordering, please use the appropriate SERIES NUMBER and specify the following:

- 1) Collar diameter – 10" or 12"
- 2) Efficiency % – refer to graph
- 3) Other options
- 4) Exact dimensions if other than shown
- 5) Static pressure and efficiency if other than shown




SUGGESTED SPECIFICATIONS

Filter shall be PERMA-HOOD™ Model (HHR250) (HHR400) (HHR500) as manufactured by the HEPA CORPORATION of Anaheim, California. Each filter shall be tested and certified to an efficiency of _____% on (0.3) (0.12) micron size particles. The initial static pressure on this filter will be no greater than _____" W.G. when operated at a velocity of 100FPM. Glass media with adhesive separators shall be used. The entire filter shall use only ozone friendly adhesives and sealants. Frame material will be anodized extruded aluminum and constructed to be rugged with exact dimensions of _____" x _____" x _____". Collar dimensions shall be (10") (12") diameter.

TESTING

HEPA CORPORATION filter ratings are based on volumetric tests as measured through the filter packs only. Every PERMA-HOOD™ brand filter is inspected and tested to customer's specifications. We test with thermally generated D.O.P. (dioctyl phthalate) in accordance with the latest industry standards (IES-RP-CC-001-86) and military standard MIL-STD-282 to meet 99.97% or better efficiency on 0.3 micron size particles. Scanned and "O" probe filters are further tested in accordance with federal standard 209. Laser testing is also offered for ULPA (.12 micron) filters and for non-D.O.P. requirements. Non-D.O.P. filters are challenged with P.S.L. or ambient air. Performance data on previous pages based on production filters.

Unassembled Cross-Section



Discover The Power Of The HEPA Energy Saver®

HEPA CORPORATION

3071 East Coronado Street
 Anaheim, California 92806-2698
 Telephone: (714) 630-5700
 Fax: (714) 630-2894

Internet: www.hepa.com/E-mail: info@hepa.com

DISTRIBUTED BY: